

COFFEE BREWING SYSTEMS

CBS-1240 Plus Brewers 1.0 GALLON BREWING SYSTEM

Shown with D448 4.0L / 1G LUXUS[®] Thermal Dispenser



PLUG AND PLAY OPERATION

Batch buttons are pre-programmed at the factory. If desired the USB port can be used to upload and download recipes.



CASCADING SPRAY DOME

Patented design provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.

DISPENSERS

CBS-1240 Plus Brewers

DISPENSERS

D451

4.0 Liter / 1 Gallon
LUXUS® Thermal
Server
L4S-10

NSF



D482

4.0 Liter / 1 Gallon
LUXUS® Sight
Gauge Server
LGS-10

NSF



D448

4.0 Liter / 1 Gallon
LUXUS® Thermal
Dispenser
L4D-10

NSF



D479

4.0 Liter / 1 Gallon
LUXUS® Sight
Gauge Dispenser
LGD-10

NSF



SERVING STATION FOR THERMAL SERVERS

A147

Single Serving
Station for
L4S-10 & LGS-10
S4S-10-1



A148

Twin Serving
Station for
L4S-10 & LGS-10
S4S-10-2



A149

Triple Serving
Station for
L4S-10 & LGS-10
S4S-10-3



All dispensers and serving stations **SOLD SEPARATELY**.



BREW BASKET DESIGN

Advanced brew basket design provides a deeper bed depth and superior thermal insulation for better extraction.



CONTEMPORARY DESIGN

Traditional FETCO core with modern design enhancements fits well in any front-of-house or back of the house application.



ECO MODE

Reduces tank temperature during periods of non-operation to cut down on electricity usage.

ACCESSORIES

CBS-1240 Plus Brewers

NOTE

Coffee brewers are available with **Plastic** or **Metal** brew basket options. Material type is of personal preference and does not affect flavor profile, however if you are looking for color identification the plastic brew baskets are the best option.

BREW BASKETS AND PAPER FILTERS

Item Number	Brew Basket	Coffee Capacity	Filter Size	Filter SKU	Filter/Case
All configurations	Standard Plastic / Stainless Steel	Up to 8oz / 227g	13" x 5"	F002	500/cs

B003218B1
13" x 5"
Stainless Steel
Brew Basket


B014218BN2BK
13" x 5"
Plastic Brew
Basket


F002
13" x 5"
Paper Filters


Contact Customer Service or your Sales Person for more options.

COLORED BREW BASKET HANDLE INSERTS

1023.00180.00 Blue Insert 	1023.00190.00 Red Insert 	1023.00191.00 Green Insert 	1023.00192.00 Orange Insert 
---	--	---	---

WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A039	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water
Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) / 1ea. 3/8" x 4' connection hose / 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve


BWT BESTMAX

In-Line Water
Filtration System



SET INCLUDES: 1ea. filter cartridge / 1ea. universal filter head / 1ea. wall mounting bracket Braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences



TECHNICAL SPECIFICATIONS

NORTH AMERICA


CBS-1241 Plus Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E1241US-1A115-MM011	13x5" Metal	100-120	1 x 1.5 kW / 120 V	1	2+G	1.1-1.6	NEMA 5-15P	10.8-12.9	4.0 / 15.1	 
E1241US-1A115-PM011	13x5" Plastic	100-120	1 x 1.5 kW / 120 V	1	2+G	1.1-1.6	NEMA 5-15P	10.8-12.9	4.0 / 15.1	 
E1241US-1X117-MM011 DUAL VOLTAGE	13x5" Metal	100-120 120/208-240	1 x 1.7 kW / 120 V 2 x 1.7 kW / 120 V	1 1	2+G 3+G	1.3-1.8 3.5	NEMA 5-15P No Cord	12.2-14.6 14.6	4.5 / 17.1 9.0 / 34.2	 
E1241US-1X117-PM011 DUAL VOLTAGE	13x5" Plastic	100-120 120/208-240	1 x 1.7 kW / 120 V 2 x 1.7 kW / 120 V	1 1	2+G 3+G	1.3-1.8 3.5	NEMA 5-15P No Cord	12.2-14.6 14.6	4.5 / 17.1 9.0 / 34.2	 
WATER										
Water Inlet		Water Pressure [psig] / [Bar]		Minimum Flow Rate [gpm] / [L/min]			Tank Capacity [Gal] / [L]			
3/8" Male Flare		20-75 / 1.37-5.17		1.50 / 5.68			4.10 / 15.50			

CBS-1242 Plus Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E1242US-1B230-MM010	13x5" Metal	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	12.2 / 46.3	NSF cULus
E1242US-1B230-PM010	13x5" Plastic	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	12.2 / 46.3	NSF cULus
WATER										
Water Inlet		Water Pressure [psig] / [Bar]		Minimum Flow Rate [gpm] / [L/min]			Tank Capacity [Gal] / [L]			
3/8" Male Flare		20-75 / 1.37-5.17		1.50 / 5.68			7.48 / 28.31			

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.



TECHNICAL SPECIFICATIONS

INTERNATIONAL

CBS-1241 Plus Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E1241IN-1B130-PM000	13x5" Plastic	200-240	1 x 3.0 kW / 240 V	1	L/N/PE	2.2-3.1	No Cord	10.8-12.9	8.0 / 30.2	 
E1241IN-1B140-PM000 ¹	13x5" Plastic	200-240	1 x 4.0 kW / 240 V	1	L/N/PE	2.9-4.1	No Cord	14.3-17.1	10.0 / 37.9	 
E1241IN-1B123-PM000 ¹	13x5" Plastic	200-240	1 x 2.3 kW / 240 V	1	L/N/PE	1.7-2.4	No Cord	8.4-10.0	6.1 / 23.2	 
E1241NM-1B140-PM000 ¹	13x5" Plastic	208-240	1 x 4.0 kW / 240 V	1	2+G	3.1-4.1	No Cord	14.8-17.1	10.0 / 37.9	 
E1241NM-1X123-PM002 DUAL VOLTAGE	13x5" Plastic	100-120 120/208-240	1 x 2.3 kW / 120 V 2 x 2.3 kW / 120 V	1	2+G 3+G	1.7-2.4 4.7	No Cord	16.4-19.6 19.6	6.1 / 23.2 10.0 / 37.9	 
E1241CE-1B130-PM000	13x5" Plastic	230	1 x 3.0 kW / 240 V	1	L/N/PE	2.9	No Cord	12.4	7.4 / 28.2	 

WATER			
Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	4.10 / 15.50

CBS-1242 Plus Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E1242IN-1B223-PM000	13x5" Plastic	200-240	2 x 2.3 kW / 240 V	1	L/N/PE	3.3-4.7	No Cord	16.4-19.6	12.2 / 46.3	 
E1242IN-1B230-PM000	13x5" Plastic	200-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.3-6.1	No Cord	21.2-25.4	15.9 / 60.4	 
E1242NM-1B230-PM000	13x5" Plastic	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	15.9 / 60.4	 
E1242CE-2B230-PM000	13x5" Plastic	230/400	2 x 3.0 kW / 240 V	2	2L/N/PE	5.6	No Cord	12.4	14.9 / 56.4	 
E1242CE-1B230-PM000	13x5" Plastic	230	2 x 3.0 kW / 240 V	1	L/N/PE	5.6	No Cord	24.4	14.9 / 56.4	 

WATER			
Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	7.48 / 28.31

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.


DIMENSIONS

CBS-1241 Plus Brewer

DIMENSIONS							WEIGHT		
	Height (A)	Width (B)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)		Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Dimensions	34.5" / 87.63 cm	11.75" / 29.84 cm	20.5" / 52.07 cm	15.13" / 38.43 cm	21.38" / 54.30 cm	12.13" / 30.80 cm	Product Weight	38 lbs / 17.2 kg	64 lbs / 29.0 kg
Shipping Dimensions	35.0" / 88.90 cm	17.0" / 43.18 cm	22.0" / 55.88 cm	N/A	N/A	N/A	Shipping Weight	50 lbs / 22.7 kg	N/A

CBS-1242 Plus Brewer

DIMENSIONS							WEIGHT		
	Height (A)	Width (C)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)		Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Dimensions	34.5" / 87.63 cm	19.75" / 50.16 cm	20.5" / 52.07 cm	15.13" / 38.43 cm	21.38" / 54.30 cm	12.13" / 30.80 cm	Product Weight	56 lbs / 25.4 kg	101 lbs / 45.8 kg
Shipping Dimensions	35.0" / 88.90 cm	22.0" / 55.88 cm	24.0" / 60.96 cm	N/A	N/A	N/A	Shipping Weight	66 lbs / 29.9 kg	N/A



FAX
+1.847.719.3001